

## TERMINAL GROUP

### ● RADIAL OIL SEAL AND V-RING

| TYPE  | PRODUCT NAME<br>(CODE)  | MATERIAL   | PRESSURE<br>MPA (kgf/cm <sup>2</sup> ) | TEMPERATURE  |
|---|---|--|--|--|
|   | - SC, SB<br>- G, M<br>- CB  | - NBR + METAL<br>- FKM + METAL<br>- VMQ + METAL    | 0.03 MPA<br>(0.3 kgf/cm <sup>2</sup> ) | -40°C TO + 100°C<br>-15°C TO + 200°C<br>-45°C TO + 200°C |
|   | - TC, TB<br>- GP, MP<br>- CC  | - NBR + METAL<br>- FKM + METAL<br>- VMQ + METAL    | 0.03 MPA<br>(0.3 kgf/cm <sup>2</sup> ) | -40°C TO + 100°C<br>-15°C TO + 200°C<br>-45°C TO + 200°C |
|   | - VC, VB<br>- GSM<br>- MSM  | - NBR (A727) + METAL                               | -                                      | -30°C TO + 120°C   |
|    | - TCN<br>- GBP  | - NBR + METAL<br>- FKM + METAL                     | 1 MPA<br>(10 kgf/cm <sup>2</sup> )     | -40°C TO + 100°C<br>-15°C TO + 200°C                     |
|    | - UN<br>- TGU   | - NBR + FABRIC<br>(TEXTILE RUBBER)<br>FKM + FABRIC | 0.05 MPA<br>(0.5 kgf/cm <sup>2</sup> ) | -20°C TO + 120°C<br>-20°C TO + 220°C                     |
|  VA  |  VS  | VA   | VS                                     | -  |
|  VL  |  RME | VL   | RME                                    | -  |
|   | OKC3Y   | - NBR + METAL                                      | 1 MPA<br>(10 kgf/cm <sup>2</sup> )     | -40°C TO + 100°C   |